



NOTES:
1. MAKE FROM 2.5" X .049" W.T. TUBE.

REVISIONS		
REV	DESCRIPTION	DATE
B	CHANGED LENGTH	6/3/2003
C	CHANGED TO 2.5" DIAMETER	7/2/2003

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES DECIMAL TOLERANCES:					
.X	±.030	.XX	±.015	.XXX	±.005
ANGULAR TOL: ± 1° SURFACE ROUGHNESS: $\sqrt{63}$					
INTERNAL AND EXTERNAL SURFACE INTERSECTIONS SHALL BE UNIFORMLY FINISHED WITH CHAMFER .005/.010 X 45° OR RADIUS .005/.010. CHAMFER ALL THREADED HOLES 110° OF MAJOR DIAMETER X 45°					
MATERIAL:	304/316/321 SST				
FINISH:	NONE				

High Precision Devices

1668 Valtec Lane, Suite C, Boulder, Colorado 80301
Phone: (303) 447-2558 Fax: (303) 447-2548 Web Site: www.hpd-online.com

TITLE: **p02101-048 Tube, LN2 can feedthru**

CONFIGURATION: **00-Default**

SIZE	QTY PER ASSM:	SCALE:	SHEET	OF	REV
A	1	1:2	1	1	C
DATE:	DRAWN BY: C. Danaher				
	5/17/2004				